

COREWELD A600

Flux cored wires [FCAW]

Hardfacing and repairing

CLASSIFICATION: EN ISO 14700-A : T Fe2 DIN 8555 : MF 6-GF-60GP	APPROVALS:	APPLICATION: Hardfacing and repairing
---	-------------------	---

- Flux cored wire recommended for hardfacing of elements exposed to very high impact and medium abrasion.
- The build-up weld is hard, smooth, resistant to distortion and impact, as well as metal-to-metal wear. It can only be machined by grinding.
- It can be used in TIG technology for precision welding of small elements.
- Possibility of hardfacing thinner elements with complex shapes.
- Structurally martensite with retained austenite and chromium carbides.

Application

Hardfacing of mixer and ship shovels, bucket teeth and grippers of excavators, hammers and crushing jaws, etc.


Base material

Steels
Cast steels

Typical chemical composition %

C	Si	Mn	Cr	Mo
0,49	0,60	1,6	5,9	0,88

Typical mechanical properties

Hardness	57-62 HRC (after welding) / The hardness of the build-up weld depends on the relevant welding conditions, the number of layers and the chemical composition of the base material /
Wire/rod type	flux cored
Welding current	
Shielding gases acc. to EN ISO 14175	C1 - 100% CO2 / M21 - Ar + 15 - 25% CO2 /
Remarks	When hardfacing the base material of easily hardened steels, steels with high carbon content, steels with limited weldability, a buffer layer should be used, e.g. of material type 307.

Welding parameters and packing

∅	Welding current [A]	Voltage [V]	Weight of packet [kg]
1,2	190-300	29,5-33,5	15,0
1,6	220-420	26-32	15,0

METALWELD-FIPROM POLSKA spółka z o.o.

ul. Mikołajczyka 57, 41-200 Sosnowiec

+48 (32) 297 75 50 - 51

+48 (32) 297 75 88

export@metalweld.pl

